

Brother's comprehensive range of RJ mobile printers can deliver impressive print speed with rugged design, robustness and superior quality that cater to a wide range of vertical market applications.

Equipped with Wireless, USB and Bluetooth® wireless connectivity options, busy mobile workers can print their receipts or labels on-site or in field which will help to achieve productivity.



RJ Series mobile printers



#### Rugged design

Due to the nature of many mobile applications, mobile printers may be exposed to a range of outdoor conditions which can affect the print operation, resulting in damage. For example, a Traffic warden printing in the field.

RJ mobile printers have been tested against IP54 protection standards which offer extra peace of mind for extreme outdoor applications expose to damp, moisture or indoor environments where dust is present. Selected RJ mobile printers were dropped and tested up to 2.5 metres which provide the additional credibility in terms of toughness and reliability.



RJ Series

# Up to 2 inch



# Up to 3 inch



# Up to 4 inch



RJ-4230B RJ-4250WB

# Trust RJ Mobile Printers Series for every application

#### Retail

Increase efficiency for retailers with lightweight, durable and easy-to-use RJ mobile printers.

This mobile solution can provide staff with a simple and accurate label and receipt printing that is ideal for pricing, promotions and queue-busting situation which will help to increase customers' satisfaction.

#### **Direct Store Deliveries**

Delivery drivers can be equipped with a seamless solution to help streamline their workflow and minimise downtime.

Mobility and integration are the keys for drivers to access their systems for pricing, invoicing, inventory control which will help to increase their customers' satisfaction.

This mobile solution can makes producing invoices on-site easy.

#### **Field Services**

Without a mobile printing solution, manually handwritten documents can be very time-consuming to produce and prone to error.

That is why most businesses are empowering their workforce with mobile technology to complete their tasks on the move, professionally and on schedule.













#### Applications include:

- Shelf edge labels
- 'Queue busting' receipt printing
- Mark down or discount labels
- Price labels
- Food traceability labelling
- Click and collect labels

#### Applications include:

- Sales orders and confirmations
- Returned goods receipts and labels
- Customers' receipts
- Delivery receipts

#### Applications include:

- Receipts and invoices
- Repair estimates
- Statements of work
- Work orders
- Estimates and quotations
- Maintenance and service reports








#### RJ Series

## **Public Safety**

Increase operational efficiency by allowing law enforcement officers and emergency staff to document and report incidents accurately and efficiently at the point of interaction.

With RJ mobile printers' durable design, fast print speed and reliable operation, superior performance can be achieved which can help to



increase productivity.





# potential errors caused by mislabelling.

Warehousing

Efficient warehousing operations and

workers' productivity are critical to the

With wireless connectivity, RJ mobile printers series can provide workers

This will help to save time and reduces

success of many organisations.



- Parking violations
- Recording of accidents and crime scenes
- Electronic citations and fines
- Warning Notices

- Work-in-progress labels
- Bin and shelf labels
- Shipping and despatch labels
- Inventory pick and return tickets







# **RJ** series range

	RJ-2030	RJ-2050	RJ-2140	RJ-2150
		<b>2</b> in	nch	
Printing				
Print technology		Direct	thermal	
Print speed		Maximum 152mm	n per second (6ips)	
Resolution		203	Bdpi	
Maximum print width	54mm (	(receipt)	54mm (receipt),	51mm (label)
Receipt	•	•	•	•
Labels			•	•
Connectivity				
USB	•	•	•	•
Wireless LAN		•	•	•
Bluetooth® wireless connection	•	•		•
AirPrint®		•	•	•
MFi®		•		•
General				
IP rating		IP54		
Drop protection (metres)		2.5m		
Weight (with battery)	46	65g	545	g
Dimensions (mm)	122mm (W) 57mm (H) 100mm (D)		151mm (W) 73mm (H) 100mm (D)	
Operating system support	Microsoft® Windows®	Microsoft® Windows® Windows® Server®		
Mobile OS	Android™		Android™, iOS®	
Supported commands	P-touch Template, ESC/P, Raster, ZPL II emulation, CPCL emulation			

# **RJ** series range

	RJ-3230B	RJ-3250WB	RJ-4230B	RJ-4250WB
	3 in	ich	4 ir	nch
Printing				
Print technology		Direct 1	hermal	
Print speed		Maximum 127n	nm per second (5ips)	
Resolution		203	Bdpi	
Maximum print width	72	mm	104	mm
Media Types				
Receipt	•	•	•	•
Labels	•	•	•	•
Connectivity				
USB	•	•	•	•
Wireless LAN		•		•
Bluetooth® wireless connection	•	•	•	•
AirPrint®		•		•
MFi <sup>®</sup>	•	•	•	•
General				
IP rating		IP.	54	
Drop protection (metres)	2.0	m	2.1	m
Weight (with battery)	807	<sup>7</sup> g	85	0g
Dimensions (mm)	117mm (W) 153mm (W) 77mm (H) 68mm (H) 159mm (D)		n (H)	
Operating system support	Microsoft® Windows® Windows® Server®		Microsoft® Windows®  RJ-4250WB also supports:  Microsoft®  Windows® Server®	
Mobile OS	Android™, iOS®			
Supported commands	P-touch Template, ESC/P, Raster, ZPL II emulation, CPCL emulation			



# **Accessories**

Brother has designed and engineered a wide range of accessories to customise solution to suite customers' requirement. Brother accessories can help workers to be equipped with their device in-vehicle and on-body. Power options can help to cope up with any increase battery demands.

# **Power Options**

#### **PA-BT-003**

#### Rechargeable Li-ion Battery

RJ-2030 | RJ-2050 RJ-2140 | RJ-2150



#### **PA-BT-006**

#### Rechargeable Li-ion Smart Battery

RJ-3230B | RJ-3250WB RJ-4230B | RJ-4250WB



#### PA-AD-600A UK

#### **AC Power Adapter**

RJ-2030 | RJ-2050 RJ-2140 | RJ-2150 RJ-3230B | RJ-3250WB RJ-4230B | RJ-4250WB



#### PA-CD-600CG

#### Car Adapter (cigarette)

RJ-2030 | RJ-2050 RJ-2140 | RJ-2150 RJ-3230B | RJ-3250WB RJ-4230B | RJ-4250WB



#### PA-CD-600WR

#### Car Adapter (wired)

RJ-2030 | RJ-2050 RJ-2140 | RJ-2150 RJ-3230B | RJ-3250WB RJ-4230B | RJ-4250WB



#### PA-BEK-001WR

#### Battery Eliminator Kit Wired Type

RJ-3230B | RJ-3250WB RJ-4230B | RJ-4250WB



#### PA-BEK-001CG

#### Battery Eliminator Kit Cigarette Socket Type

RJ-3230B | RJ-3250WB RJ-4230B | RJ-4250WB



Accessories availability differ by country. Please contact your local Brother Sales office for the accessories available.









#### **Accessories**

#### PA-BC-002 PA-BC-003 PA-CR-005\*\* PA-CR-002A\*\* **Battery Charger Battery Charger** 1-slot Charging Car Mount / (Single unit) (Single unit) Cradle with Ethernet **Charging Cradle** RJ-2030 | RJ-2050 RJ-3230B | RJ-3250WB RJ-4230B | RJ-4250WB RJ-3230B RJ-3230B | RJ-3250WB RJ-2140 | RJ-2150 RJ-4230B | RJ-4250WB RJ-3250WB RJ-4230B | RJ-4250WB

#### PA-4CR-003\*\* PA-LPR-001 PA-LPR-004 **PA-LP-007** 4-slot Charging Linerless Linerless Peeler Cradle with Ethernet Platen Roller Platen Roller RJ-3230B RJ-4230B RJ-3230B RJ-3230B RJ-3250WB RJ-3250WB RJ-3250WB RJ-4250WB

Accessories availability differ by country. Please contact your local Brother Sales office for the accessories available.







PA-SS-4000

**Shoulder Strap** 

RJ-2030 | RJ-2050 RJ-2140 | RJ-2150 Brother provides all the necessary tools required for software developers to integrate printing into their mobile applications.

Printer drivers are available for Windows® OS and Software Development Kits (b-Pac SDK). RJ mobile printers support Windows® Mobile\*, Android™ and iOS® operating system.

Software Support Features


### **Template mode**

Design required document on Windows® PC with logos and barcodes. Stored in RJ mobile printer's memory after transferred.

Templates can be recalled and data replaced before printing in just a few short commands.

# AirPrint®\* and MFi®\* support

Easy to connect and print from Apple® devices via AirPrint® and MFi® support.







#### **Mobile Deploy\***

Cloud-based app for mobile devices running on  $iOS^{\circledast}$  and Android<sup>TM</sup> platforms allows IT administrators to remotely update and configure multiple Brother RJ mobile printers.

Use Mobile Deploy to easily upload new update packages to an online location and share the URLs with the users.


https://support.brother.com/g/s/es/dev/en/index.html

#### **Printer Commands\***

With support for ZPL II emulation, CPCL emulation in addition to the ESC-POS commands, developers can easily integrate mobile printing into any existing legacy systems.



# **Mobile Deploy**







# **RJ** series range 2 inch 2 inch

# **Printing / Media**

Direct thermal			
203dpi			
Maximum 152m	m per second (6ips)*		
54	mm		
100	0mm		
Reflective Transmissive / Reflective			
Tear bar			
Receipt, label** Receipt, label, tag label			
58mm max			
2.3mils - 3.5 mils (0.058mm - 0.090mm)			
-	55mm		
-	3.1mils - 6.7 mils (0.080mm - 0.170mm)		
40mm max 60mm max			
10.2mm			
	20:  Maximum 152m 54  100  Reflective  Teal  Receipt, label**  58m  2.3mils - 3.5 mils (		

## **LCD**

Туре Backlit monochrome LCD

# Connectivity

USB	USB version 2.0 full-speed (mini-B connector)				
Bluetooth® wireless connection	Bluetooth® Classic				
Bluetooth® profiles	SPP (Serial Port Profile) OPP (Object Push Profile) BIP (Basic Imaging Profile) HCRP (Hard Copy Cable Replacement Profile)		SPP (Serial Port Profile) OPP (Object Push Profile) BIP (Basic Imaging Profile) HCRP (Hard Copy Cable Replacement Profile) iAP supported		
MFi® support	-	Yes -		Yes	
Wireless LAN	-	IEEE 802.11b/g/n Infrastructure mode: b/g/n Ad hoc mode: b/g/n Wireless direct mode: g/n			
Wireless LAN security (Ad hoc mode)	-	None / WEP			
		None / WEP64 / WEP128			
Wireless LAN security (Infrastructure mode)	-	Common key authentication (WEP)  WPA / WPA2-PSK (TKIP + AES)  LEAP (CKIP)  EAP-FAST (TKIP / AES)  PEAP (TKIP / AES) *3  EAP-TLS (TKIP / AES)  EAP-TTLS (TKIP / AES)			
Wireless LAN security (Wireless direct mode)	-	None / WPA2-PSK (AES) / WEP			
NFC		-			

<sup>\*</sup> Under Brother standard environment. \*\* With black mark only.

RJ series range 2 inch	RJ-2030	RJ-2050	RJ-2140	RJ-2150		
Software / Firmware	2 inch					
Operating system support	Microsoft® Windows® Android™	Microsoft® Windows® Windows® Server® Android™ iOS®				
b-Pac SDK availability https://support.brother.com/g/s/es/dev/en/index.html			OK (for Windows®) Android™ iOS®			
Supported printer commands			tion, CPCL emulation uch Template, Raster			
Barcode symbologies	CODE39 / ITF (I-2/5) / EAN-13 / EAN-8 / UPC-A / UPC-E / CODABAR / CODE128 / GS1-128(UCC/EAN-128) / RSS symbols / CODE93 / POSTNET / UPC/EAN EXTENSION / MSI /  QR Code (model 1, model 2, micro QR) / PDF417 (Standard, Truncate, MicroPDF417) / Data Matrix (ECC200 Square, ECC200 Rectangular) / MaxiCode / Aztec					
Memory						
RAM			2MB			
Flash		32MB (12MB availal	ole for template upload)			
Environmental						
Drop protection			5m			
Sealing Operating temperature			P54 50°C / Charging: 0°C to 40°C			
Operating humidity	10% - 90% / Maximum wet bulb: 27°C (no condensation)					
Storage temperature	-20°C to 60°C for 120 hours maximum					
Storage humidity		45°C @ 95%	for 120 hours maximum			
Power						
Battery	Rechargeable Li-ion					
AC Power adapter	100V - 240V AC (50Hz / 60Hz) to 15V DC (only for charging) (optional)					
Car adapter (optional accessory)	12V DC (only for charging)					
Weights / Dimensions						
Dimensions (mm)	122mm (W) x 57	'mm (H) x 100mm (D)	151mm (W) x 73m	nm (H) x 100mm (D)		
Weight (including battery)	4	65g	54	45g		
Package content Included in the box	Battery, belt clip, documentation					

# RJ series range 3 and 4 inch RJ-3250WB RJ-4250WB 3 inch 4 inch

# Printing / Media

Direct thermal			
203dpi			
Maximum 127m	m per second (5ips)		
72mm 104mm			
300	)0mm		
Transmissive / Reflective			
Double tear bar			
Receipt / Label / Tag label			
80mm	113mm		
2.2 mil to 3.5 mil (0.058mm to 0.090mm)			
76mm	113mm		
-	3.1 mil to 6.6 mil (0.080mm to 0.170mm)		
66mm max	58mm max		
Standard : 25.4mm (Default) In-box: 12.7mm - 13.0mm or 19.0mm			
	203  Maximum 127m 72mm  300  Transmissive  Double  Receipt / La  80mm  2.2 mil to 3.5 mil (0  76mm  - 66mm max  Standard : 25.4mm (Default)		

## LCD

Type Monochrome

# Connectivity

Commodating				
USB	Yes (USB Type-C)		Yes	
USB host capability	No		-	
Bluetooth® wireless connection	Bluetooth® Dual-Mode		Bluetooth® Dual-Mode	
Bluetooth® profiles	SPP (Serial Port Profile) OPP (Object Push Profile) HCRP (Hard Copy Cable Replacement Profile) iAP supported Low Energy: GATT		Classic: SPP (Serial Port Profile) OPP (Object Push Profile) HCRP (Hard Copy Cable Replacement Profile) iAP supported Low Energy: GATT	
MFi® support		Yes		
Wireless LAN	-	IEEE 802.11a/b/g/n/i/r Infrastructure mode: IEEE 802.11a/b/g/n/i/r Wireless Direct mode: IEEE 802.11g/n/d/i	-	Wireless LAN IEEE 802.11 a/b/g/n (Infrastructure mode: a/b/g/n / Wireless direct mode: [g/n])
Wireless LAN security (Ad hoc mode)	-	-	-	
Wireless LAN security (Infrastructure mode)	-	SSL / TLS1.0 / 1.1 / 1.2 (HTTPS, IPPS) SNMPV3, 802.1x (EAP-FAST, PEAP, EAP-TLS, EAP-TTLS) WEP 64 / 128 bit, WPA-PSK (TKIP / AES), WPA2-PSK (AES), WPA3-SAE (AES)	-	Open system (None / WEP64 / WEP128) Common key authentication (WEP) WPAWPA2-PSK (TKIP + AES) EAP-FAST (TKIP / AES) PEAP (TKIP / AES) EAP-TLS (TKIP / AES) EAP-TTLS (TKIP / AES)
Wireless LAN security (Wireless direct mode)	WPA2-PSK (AES)		-	WPA2-PSK (AES)
NFC	Yes (Passive only)			

<sup>\*</sup> Black mark only.

RJ series range 3 and 4 inch	RJ-3250WB 3 inch		RJ-4230B	RJ-4250WB	
Software / Firmware					
Operating system support		° Windows® °° Server®	Microsoft® Window®	Microsoft® Windows® Microsoft® Windows® Server®	
For latest OS system Visit: https://support.brother.com					
b-Pac SDK availability https://support.brother.com/g/s/es/dev/en/index.html		droid <sup>TM</sup> iOS®		roid™ OS®	
Supported printer commands			ouch Template, ZPL II CPCL emulation		
Barcode symbologies  Supported barcodes depend on printer commands. Please refer to the command reference for details.	CODE39, CODE93, ITF (I-2/5), EAN-8, EAN-13, UPC-A, UPC-E, CODABAR (NW-7), CODE128, GS1-128 (UCC/EAN-128), GS1 DataBar (Standard, Truncated, Stacked, Stacked Omnidirectional), GS1 DataBar Limited, GS1 DataBar Expanded (Standard, Stacked), POSTNET, UPC/EAN EXTENSION, MSI, Intelligent Mail Barcode, QR Code, Micro QR Code, PDF417, MicroPDF417, MaxiCode, DataMatrix, Aztec		Linear: CODE 39, ITF (I-2/5), EAN-8, EAN-13, UPC-A, UPC-E, UPC/EAN EXTENSION CODABAR, CODE 128, GS1-128 (UCC/EAN 128), POSTNET, GS1 Databar (Omnidirectional / Truncated / Stacked / Stacked Omnidirectional / Limited / Expanded / Expanded Stacked) CODE93, MSI/Plessey Inteligent Mail Barcode  2-dimensional: QR Code (model 1, model 2, micro QR), Maxi code, PDF417 (Standard, Truncate) MicroPDF417, Data Matrix (Square, Rectangular) AztecCode		
Memory RAM		256	SMB		
Flash	128MB			4MB	
Environmental Drop protection		2m	2	.1m	
Sealing		IP	54		
Operating temperature		20°C to 55°C : 0°C to 40°C	Battery: -20°C to 55°C AC Power adapter: -10°C to 40°C. Car adapter: -10°C to 50°C		
Operating humidity	10% to 90% non-condensing		10% - 90%, Max wet bulb: 27°C (No condensation)		
Storage temperature	-20°0	to 60°C	-20°C to 60°C		
Storage humidity	10% - 90% non-condensing		10% - 90%, Max wet bulb: 45°C (No condensation)		
Power Battery	Rechargeable	.i-ion smart battery	Rechargeable Li-ion	smart battery (optional)	
AC Power adapter	AC Power adapter (15V) only for charging (optional)		AC Power adapter (15V) only for charging (50 / 60Hz) (optional)		
Car adapter (optional accessory)	(0)		type (12V (DC)) only for charging	L, (optional)	
Weights / Dimensions Dimensions (mm)	117mm (M) v 77	mm (H) x 180mm (D)	153mm (M) v 68r	nm (H) x 159mm (D)	
Weight (including battery)		117mm (W) x 77mm (H) x 180mm (D) 807g		350g	
Package content					
Included in the box	Mobile Printer Belt Clip Rechargeable Li-ion battery Roll Holder Stop Documentation		Bel	e Printer t clip uide lockers	





#### **BROTHER INTERNATIONAL (VIETNAM) CO., LTD**

Ho Chi Minh: 5th Floor - Minh Long Building, 17 Ba Huyen Thanh Quan Street, Xuan Hoa Ward Tel: (028) 6 290 8787 | Fax: (028) 6 290 8786 | Ha Noi: 5th Floor, 352 Hue Street, Le Dai Hanh, Hai Ba Trung | Tel: (024) 3 972 071 | Website: www.brother.com.vn | Hotline: 1900 6062